

Data Sheet of gaZalarm Ox



TECHNICAL SPECIFICATION :

Control Card	Solid State Electronics Base
Display	2/3 Digit LED
Measuring Range	0 - 25 / 100% Vol / 0 - 1000 ppm.
Size	Din Standard - 3U X 6T/9T - Depth - 220 mm
Accuracy	1% of FSD
Ambient Oper. Temp.	0 - 50 deg C
Visual Indication	A) Alarm B) Warn C) Power D) Fault
Controls	A) Reset B) Accept C) Lamp Test
Parameter Setting	A) Zero B) Span C) Warn D) Alarm
Input Signals	Standard: - 4 - 2 mA. (3 wire, 2 wire) Optional: - 0 - 1 cDC
Outputs	Standard: - 4- 20 mA. Recorder Output, Potential free Relay contacts for warn, Alarm & Faults. Optional: - Repeater output for warn, Alarm & Fault, 0 - 1 vDC.
Power Supply	Standard: - 220 Vac. 50 Hz Optional: - 110 vAC. OR 24 vDC.
Mounting	19" Rack (DIN Standard) for Max. Upto 10 cards or as per specification
Panel	Standard: Wall Mounted / Free Standing Optional: As per specification

Note:

v For quotation or any other information email at:

polutn.purvi@vsnl.com

ptpl@bom5.vsnl.net.in