

## Data Sheet of gaZguard Ox

### APPROVALS

- Certified for Intrinsically safe as per IS 5780 (ERTL East)
- Certified for Performance as per IS 9000 (ERTL West)
- BIS Certificate No: - CM / L 7449687 as per IS: 5780
- CCE Approval No: -A/P/HQ/MH/104/518(P55545)



### TECHNICAL SPECIFICATION :

Dimension	130mm x 67mm (4.5" x 2.6" x 1.6")
Weight	450 gms. (With Batteries)
Accessories	Standard:- Carrying Case Batt. Charger Optional Aspirator adaptor
Sensor Type	Electrochemical / Semiconductor
Sensor Life	2 to 3 years (in fresh air)
Measurement Range	0-25% vol.
Display	3 ½ Digit standard alarm levels.
Resolution	0.1%
Response Time	T95 < 15 Sec.
Standard Alarm Levels	LO - 19.5% HI - 22.5%
Optional Alarm Indication	As per specification
Alarm Indication	Pulsating / Continuous red LED with audible, 90 db at 1 Meter
Battery	Standard: Rechargeable 4 X AA cells Optional: Disposable
Battery Life	12 - 15 hrs. Continuous
Oper. Temperature	-10 deg C to 50 deg C. (14 deg F to 122 deg F)
Humidity	0 - 95% RH Non - Condensing
Setting	Zero / Span accessible from outside

#### Note:

v For quotation or any other information email at:

polutn.purvi@vsnl.com

ptpl@bom5.vsnl.net.in